


TOP-DISCHARGE CONDENSING UNIT - CA SERIES

# Top-Discharge Condensing Unit - CA Series




**1. With Sanyo-Panasonic Compressor Installed,** produce stronger power and stable operation. Also with Anti-attenuation design and better low-temperature heating performance.



**4. Versatile.** You can match it with any indoor unit (AHB, CSA, FUA and FCA Series)

**2. Universal Design,** convenient for market stocks and spare parts.



**5. 24V Universal Communication Connection,** safe and simple.



**3. Metal grille** for best coil protection.



**6. Multi-Protection:** High pressure protection, low pressure protection, and exhausted temp.

Model		CA-2413	CA-3613	CA-4813	CA-6013
Power Supply	V/Hz/Ph	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
<b>Capacity</b>					
Cooling	Btu/h	24000	36000	48000	60000
	RT	2	3	4	5
<b>Physical Data</b>					
Air Flow Volume	CFM	2400	2400	3200	3200
Noise Level	dB(A)	60	60	65	65
Net Dimension (WxDxH)	Inches	21 3/4"x21 3/4"x24 7/8"	21 3/4"x21 3/4"x24 7/8"	29 1/8"x 29 1/8"x32 7/8"	29 1/8"x 29 1/8"x32 7/8"
Packing Dimension (WxDxH)	Inches	22 5/8"x22 5/8"x26"	22 5/8"x22 5/8"x26"	29 7/8"x29 7/8"x32 7/8"	29 7/8"x29 7/8"x32 7/8"
Net Weight	Lbs	105	114	178	216
Gross Weight	Lbs	112	121	182	224
Compressor	Type	Rotary	Rotary	Scroll	Scroll
	Brand	Sanyo - Panasonic	Sanyo - Panasonic	Sanyo - Panasonic	Sanyo - Panasonic
<b>Piping Data</b>					
Liquid Size	Inches	3/8"	1/2"	3/8"	3/8"
Gas Size	Inches	5/8"	3/4"	3/4"	3/4"
<b>Loading</b>					
Loading Qty (20' / 40' / 40' HQ)	Pcs	140/288/288	72/162/162	57/117/120	57/117/120



Distributed by \_\_\_\_\_