


 **everwell**[®]




FLOOR & CEILING UNIT - FCA SERIES

Floor & Ceiling Unit - FCA Series



1. Flexible Installation, ceiling suspended and floor standing.




4. LED Display, more intuitive, and simple error code shown in display.



2. Washable Air Filter.



5. New Upper and Lower Buckle Type Wheel Case, can be removed alone, which is convenient to adjust the wheel motor.



3. Auto-Swing Function, built-in two louver motor, vertical and horizontal air-flow adjustment.

Model			FCA-18	FCA-24	FCA-36	FCA-48	FCA-60
Power Supply		V/Hz/Ph	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Capacity							
Cooling Capacity	Capacity	Btu/h	18000	24000	36000	48000	60000
		RT	1.5	2	3	4	5
Physical Data							
Air Flow Volume (Hi/Med/Low)		CFM	450/330/210	880/760/640	880/760/640	1230/1110/1000	1230/1110/1000
Noise Level (Hi/Med/Low)		dB(A)	50/48/45	50/48/45	50/48/45	57/54/51	56/54/48
Net Dimension (WxHxD)		Inches	34 5/8"x26 3/4"x8 7/8"	49"x26 3/4"x8 7/8"	49"x26 3/4"x8 7/8"	65 3/4"x26 3/4"x9 5/8"	65 3/4"x26 3/4"x9 5/8"
Packing Dimension (WxHxD)		Inches	37 3/4"x30 1/4"x12 3/4"	52 1/8"x30 1/4"x12 3/4"	52 1/8"x30 1/4"x12 3/4"	68 7/8"x30 1/4"x12 3/4"	68 7/8"x30 1/4"x12 3/4"
Net Weight		Lbs	66	77	77	103	103
Gross Weight		Lbs	77	90	90	119	119
Applicable Area		m2	20-35	28-50	42-70	56-93	70-107
Piping Data							
Piping Size	Liquid	Inches	1/4"	3/8"	3/8"	3/8"	3/8"
	Gas	Inches	1/2"	5/8"	3/4"	3/4"	3/4"
	Drainage	Inches	1"	1"	1"	1"	1"
Loading							
Loading Qty (20' / 40' / 40' HQ)		Pcs	115/250/320	70/162/162	70/162/162	65/135/150	65/135/150



Distributed by _____